

BYK-333

Silicone-containing surface additive for solvent-free, solvent-borne and aqueous coating systems, printing inks and adhesive systems as well as ambient-curing plastic systems. Strong reduction of surface tension.

Product Data

Composition

Polyether-modified polydimethylsiloxane.

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 1.04 g/ml

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

Separation or turbidity may occur at temperatures below 5 °C. Warm to 20 °C and mix well.

Applications

Coating and Printing Ink Industry

Special Features and Benefits

The additive provides a strong reduction of the surface tension of the coatings and printing inks. It therefore particularly improves substrate wetting and avoids cratering. Surface slip and gloss are also increased. In aqueous systems it improves the anti-blocking properties.

Recommended Use

The additive is particularly recommended for all solvent-borne, solvent-free and aqueous coatings, printing inks and overprint varnishes.

Recommended Levels

0.05-0.3 % additive (as supplied) based upon total formulation. In aqueous and UV systems up to 1 %.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests. Dilution before processing can make it easier to dose.

Incorporation and Processing Instructions

The additive can be incorporated during any stage of the production process, including post-addition.

Special Note

Unlike so-called silicone oils, this additive is very user-friendly. Nevertheless, it should be determined in a series of tests whether foam is stabilized in certain systems. Similarly, the recoatability and cratering should be checked.

Adhesives & Sealants

Special Features and Benefits

BYK-333 is a highly effective silicone additive. It provides a strong reduction of surface tension, thereby improving the wetting of critical substrates.

Recommended Use

It is particularly recommended for improving the substrate wetting of adhesive systems based on polyurethanes, epoxies and acrylates.

Recommended Levels

0.05-0.3 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be incorporated during any stage of the production process, including post-addition.

Special Note

Unlike so-called silicone oils, this additive is very user-friendly. Nevertheless, its influence on the adhesive properties should be checked.

Ambient-curing Plastic Systems

Special Features and Benefits

BYK-333 is a highly effective silicone additive. It provides a strong reduction of surface tension, thereby improving the wetting of critical substrates.

Recommended Use

It is particularly recommended for improving the substrate wetting of ambient-curing polyurethane and epoxy based systems.

Recommended Levels

0.05-0.3 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be incorporated during any stage of the production process, including post-addition. It has proven successful to add the additive at the end of the process to avoid any foam stabilization.

Special Note

In comparison with so-called silicone oils, this additive is very user-friendly. Nevertheless, it should be determined in a series of tests, whether surface defects occur in certain systems.

BYK-333

Data Sheet
Issue 11/2012

BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735
info@byk.com
www.byk.com/additives

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYPK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

This issue replaces all previous versions – Printed in Germany